




CONSULTING GmbH



part of the  
Virtual  
Library

© Dr. Rüdiger Paschotta  
Last update: 2008-07-13

# Encyclopedia of Laser Physics and Technology

Home			New articles		Spotlight			Feedback			Advertising		
Categories			Search		Quiz			Links			Page hits		
A	B	C	D	E	F	G	H	I	J	K	L	M	
N	O	P	Q	R	S	T	U	V	W	X	Y	Z	

## Q Factor [previous](#) | [next](#) | [feedback](#)

Definition: a measure of the damping of resonator modes

The *Q factor* (quality factor) of a resonator is a measure of the strength of the damping of its oscillations, or for the relative linewidth. The term was originally developed for electronic circuits, e.g. LC circuits, and for microwave cavities, but later also became common in the context of optical resonators.

There are actually two different common definitions of the *Q factor* of a resonator:

- Definition via energy storage: the *Q factor* is  $2\pi$  times the ratio of the stored energy to the energy dissipated per oscillation cycle, or equivalently the ratio of the stored energy to the energy dissipated per radian of the oscillation. For a microwave or optical resonator, one oscillation cycle is understood as corresponding to the field oscillation period, not the round-trip period.
- Definition via resonance bandwidth: the *Q factor* is the ratio of the resonance frequency  $\nu_0$  and the full width at half-maximum (FWHM) bandwidth  $\delta\nu$  of the resonance:

$$Q = \frac{\nu_0}{\delta\nu}$$

Both definitions are equivalent only in the limit of weakly damped oscillations, i.e. for high *Q* values. The term is mostly used in that regime.

### Q Factor of an Oscillator

The term *Q factor* is sometimes also applied to continuously operating *oscillators*, such as active optical frequency standards. In that case, only the definition via the bandwidth can be used; the bandwidth is then the linewidth of the output signal.

If the oscillator is based on some resonator (which is virtually always the case), the effective *Q factor* of the oscillator may deviate substantially from the intrinsic *Q* value of the resonator. Particularly

This encyclopedia is provided by  
RP Photonics Consulting GmbH.

RP Photonics

You can get technical consulting from  
the author, Dr. Rüdiger Paschotta.

RP Fiber Power 2.0

This software is a  
powerful tool for  
designing fiber  
amplifiers and  
fiber lasers.

See the  
comprehensive description!

Field Guide to Lasers

This compact book by Dr. Paschotta  
explains principles and types of lasers.

Onefive

Low-noise  
femtosecond,  
picosecond,  
and tunable single-frequency lasers  
for OEM and R&D applications.


A.L.S. GmbH

Picosecond  
laser diodes  
<30 ps, 375 –  
1600 nm, >1 Wp, single shot – 120 MHz

Your Advertisement at This Place

will be seen by many thousands of  
visitors per month. These banners  
receive far over 100'000 page hits per  
month. Check the details.

U.S. Patent Application No.  
10/550,536



measurements on atomic transitions (such as in a cesium atomic clock) have a limited measurement time, so that the effective linewidth of the reference transition is increased. (This problem can be severe for cesium clocks; cesium fountain clocks represent a significant advance towards longer measurement times.) On the other hand, a carefully stabilized oscillator can have a linewidth which is a tiny fraction of the linewidth of the underlying frequency standard; for cesium atom clocks, the quartz oscillator is often stabilized e.g. to a millionth of the linewidth of the signal from the cesium beam apparatus. Effectively, the good short-term stability of the quartz oscillator is combined with the high accuracy and low long-term drift of the cesium apparatus.

### Q Factor of an Optical Resonator

The Q factor of a resonator depends on the optical frequency  $\nu_0$ , the fractional power loss  $I$  per round trip, and the round-trip time  $T$ :

$$Q = \nu_0 T \frac{2\pi}{I}$$

(assuming that  $I \ll 1$ ). For a resonator consisting of two mirrors with air (or vacuum) in between, the Q factor rises as the resonator length is increased, because this decreases the energy loss per optical cycle. However, extremely high Q values (see below) are often achieved not by using very long resonators, but rather by strongly reducing the losses per round trip. For example, very high Q values are achieved with whispering gallery modes of tiny transparent spheres (see below).

### Important Relations

The Q factor of a resonator is related to various other quantities:

- The Q factor equals  $2\pi$  times the exponential decay time of the stored energy times the optical frequency.
- The Q factor equals  $2\pi$  times the number of oscillation periods required for the stored energy to decay to  $1/e$  (~37%) of its initial value.
- The Q factor of an optical resonator equals the finesse times the optical frequency divided by the free spectral range.

### High-Q Resonators

One possibility for achieving very high Q values is to use supermirrors with extremely low losses, suitable for ultra-high Q factors of the order of  $10^{11}$ . Also, there are toroidal silica microcavities with dimensions of the order of  $100\mu\text{m}$  and Q factors well

above  $10^8$ , and silica microspheres with whispering gallery resonator modes exhibiting Q factors around  $10^{10}$ .

High-Q optical resonators have various applications in fundamental research (e.g. in quantum optics) and also in telecommunications (e.g. as optical filters for separating WDM channels). Also, high-Q reference cavities are used in frequency metrology, e.g. for optical frequency standards. The Q factor then influences the precision with which the optical frequency of a laser can be stabilized to a cavity resonance.

## The Q Factor in Laser Physics

When the Q factor of a laser resonator is abruptly increased, an intense laser pulse (*giant pulse*) can be generated. This method is called *Q switching*.

High-Q laser resonators can be used for obtaining laser output with a very narrow linewidth.

Dear user of this encyclopedia,


Trying to constantly improve this resource, RP Photonics would greatly appreciate your feedback. You may be able to indicate points of insufficient clarity, to report errors, or to suggest additions – concerning new articles, helpful equations, links to useful references, etc. The simplest way to deliver feedback is the feedback form. A link to this form is found to the right of each article heading. You may stay anonymous, if you wish so.

See also: optical resonators, bandwidth, finesse, free spectral range, Q switching, reference cavities, optical frequency standards

Category: resonators

---

Since October 2008, the Encyclopedia of Laser Physics and Technology is also available in the form of a **two-volume book**. Maybe you would enjoy reading it also in that form! The print version has a carefully designed layout and can be considered a must-have for any institute library, laser research group, or laser company.



You may order the print version via Wiley-VCH.